


Carretos	Z	de	dp	S			D			T		
				dm	D ₁	A	dm	D ₂	A	dm	D ₃	A
3/8" x 7/32" 9,525 x 5,72 mm (06B - 1 - 2 - 3)	8	28,6	24,89	15	8	20	15	8	25	15	8	32
	9	31,5	27,85	18	8	20	18	8	25	18	8	32
	10	34,5	30,82	20	8	20	20	8	25	20	10	32
	11	37,5	33,80	22	8	25	22	10	30	22	12	35
	12	40,5	36,80	25	8	25	25	10	30	25	12	35
	13	43,5	39,80	28	10	25	28	10	30	28	12	35
	14	46,5	42,80	31	10	25	31	10	30	31	12	35
	15	49,5	45,81	34	10	25	34	10	30	34	12	35
	16	52,5	48,82	37	10	28	37	12	30	37	12	35
	17	55,5	51,83	40	10	28	40	12	30	40	12	35
	18	58,6	54,85	43	10	28	43	12	30	43	12	35
	19	61,6	57,87	45	10	28	46	12	30	46	12	35
20	64,6	60,89	46	10	28	49	12	30	49	12	35	
21	67,6	63,91	48	12	28	52	16	30	52	16	40	
22	70,6	66,93	50	12	28	55	16	30	55	16	40	
23	73,7	69,95	52	12	28	58	16	30	58	16	40	
24	76,7	72,97	54	12	28	61	16	30	61	16	40	
25	79,7	76,00	57	12	28	64	16	30	64	16	40	
26	82,7	79,02	60	12	28	67	16	30	67	16	40	
27	85,7	82,04	60	12	28	70	16	30	70	16	40	
28	88,8	85,07	60	12	28	73	16	30	73	16	40	
29	91,8	88,09	60	12	28	76	16	30	76	16	40	
30	94,8	91,12	60	12	28	79	16	30	79	16	40	
31	97,9	94,15	65	14	30	80	16	30	80	16	40	
32	100,9	97,17	65	14	30	80	16	30	80	16	40	
33	103,9	100,20	65	14	30	80	16	30	80	16	40	
34	106,9	103,23	65	14	30	80	16	30	85	16	40	
35	110,0	106,26	65	14	30	80	16	30	85	16	40	
36	113,0	109,29	70	16	30	90	16	30	90	16	40	
37	116,0	112,32	70	16	30	90	16	30	90	16	40	
38	119,0	115,34	70	16	30	90	16	30	90	16	40	
39	122,1	118,37	70	16	30	90	16	30	90	16	40	
40	125,1	121,40	70	16	30	90	16	30	90	16	40	
41	129,0	124,43	78	16	35	88	20	50	-	-	-	
42	132,1	127,46	78	16	35	88	20	50	-	-	-	
43	135,1	130,49	78	16	35	88	20	50	-	-	-	
44	138,1	133,52	78	16	35	88	20	50	-	-	-	
45	141,1	136,54	78	16	35	88	20	50	88	20	60	
46	144,2	139,58	78	16	35	88	20	50	-	-	-	
47	147,2	142,61	78	16	35	88	20	50	-	-	-	
48	150,2	145,64	78	16	35	88	20	50	-	-	-	
49	153,3	148,66	78	20	35	88	20	50	88	20	60	
50	156,3	151,69	78	20	35	88	20	50	88	20	60	
51	159,3	154,72	78	20	35	88	20	50	-	-	-	
52	162,4	157,75	78	20	35	88	20	50	-	-	-	
53	165,4	160,78	78	20	35	-	-	-	-	-	-	
54	168,4	163,82	78	20	35	88	20	50	-	-	-	
55	171,4	166,85	78	20	35	88	20	50	-	-	-	
56	174,5	169,88	78	20	35	88	20	50	-	-	-	
57	177,5	172,91	78	20	35	88	20	50	88	25	60	
58	180,5	175,93	78	20	35	-	-	-	-	-	-	
59	183,6	178,96	78	20	35	-	-	-	-	-	-	
60	186,6	181,99	78	20	35	88	20	50	88	25	60	
61	189,6	185,00	78	20	35	-	-	-	-	-	-	
62	192,7	188,06	78	20	35	-	-	-	-	-	-	
63	195,7	191,10	78	20	35	-	-	-	-	-	-	
64	198,7	194,12	78	20	35	88	25	50	-	-	-	
65	201,8	197,15	78	20	35	88	25	50	-	-	-	
68	210,8	206,24	78	20	35	-	-	-	-	-	-	
69	213,6	209,26	78	20	35	88	25	50	-	-	-	
70	216,9	212,30	78	20	35	88	25	50	-	-	-	
72	222,9	218,60	78	20	35	88	25	50	-	-	-	
76	235,1	230,49	78	20	35	88	25	50	88	25	60	
80	247,2	242,61	88	25	40	108	25	50	-	-	-	
85	262,4	257,77	88	25	40	108	25	50	-	-	-	
90	277,5	272,93	88	25	40	108	25	50	-	-	-	
95	292,7	288,08	88	25	40	108	25	50	120	25	60	
100	307,8	303,25	100	25	40	108	25	50	-	-	-	
114	350,3	345,68	100	25	40	108	25	50	-	-	-	
120	368,5	363,86	100	25	40	-	-	-	-	-	-	
125	383,6	379,02	100	25	40	-	-	-	-	-	-	

para corrente de rolo
segundo DIN 8187
ISO/R 606



CARRETO mm

Raio dente r ₃	10
Largura raio C	1
Largura dente carreto B ₁	5,3
Largura dente carreto b ₁	5,2
Largura dente carreto B ₂	15,4
Largura dente carreto B ₃	25,6

CORRENTE mm

Passo	9,525
Largura interna	5,72
Rolo - ø	6,35

Material C 43

