

Polias Trapezoidais para Bússola Cônica

SPC / C - 4 GORNES

Referência	Nº Gornes	Diâmetro Primitivo	Diâmetro Externo	Tipo	Bussola Nº	Furo Máximo	E	F	J	K	L	M	N
SPC 180-04	4	180,0	189,6	3	3020	75	-	111	126	30	51	30	-
SPC 190-04	4	190,0	199,6	3	3020	75	-	111	136	30	51	30	-
SPC 200-04	4	200,0	209,6	3	3020	75	-	111	144	30	51	30	-
SPC 212-04	4	212,0	221,6	3	3020	75	-	111	156	30	51	30	-
SPC 224-04	4	224,0	233,6	3	3535	90	-	111	168	11	89	11	-
SPC 236-04	4	236,0	245,6	3	3535	90	-	111	180	11	89	11	-
SPC 250-04	4	250,0	259,6	3	3535	90	-	111	194	11	89	11	-
SPC 265-04	4	265,0	274,6	3	3535	90	-	111	209	11	89	11	-
SPC 280-04	4	280,0	289,6	3	3535	90	-	111	224	11	89	11	-
SPC 300-04	4	300,0	309,6	6	3535	90	20	111	244	11	89	11	170
SPC 315-04	4	315,0	324,6	6	3535	90	20	111	259	11	89	11	170
SPC 335-04	4	335,0	344,6	6	3535	90	20	111	279	11	89	11	170
SPC 355-04	4	355,0	365,0	6	3535	90	20	111	299	11	89	11	170
SPC 375-04	4	375,0	384,6	6	3535	90	25	111	319	11	89	11	170
SPC 400-04	4	400,0	409,6	5	3535	90	-	111	344	11	89	11	170
SPC 425-04	4	425,0	434,6	5	3535	90	-	111	369	11	89	11	170
SPC 450-04	4	450,0	459,6	5	3535	90	-	111	394	11	89	11	170
SPC 475-04	4	475,0	484,6	5	3535	90	-	111	419	11	89	11	170
SPC 500-04	4	500,0	509,6	5	3535	90	-	111	444	11	89	11	170
SPC 530-04	4	530,0	539,6	5	4040	100	-	111	474	11	89	11	170
SPC 560-04	4	560,0	569,6	5	4040	100	-	111	504	4,5	102	4,5	200
SPC 630-04	4	630,0	639,6	4	4545	110	-	111	574	1,5	114	1,5	225
SPC 800-04	4	800,0	809,6	4	5050	125	-	111	737	4	127	12	245
SPC 1000-04	4	1000,0	1009,6	4	5050	125	-	111	937	1	127	12	245
SPC 1250-04	4	1250,0	1259,6	4	5050	125	-	111	1187	4	127	12	245

SPC / C - 5 GORNES

Referência	Nº Gornes	Diâmetro Primitivo	Diâmetro Externo	Tipo	Bussola Nº	Furo Máximo	E	F	J	K	L	M	N
SPC 180-05	5	180,0	189,6	3	3020	75	-	136	130	42,0	51	42,0	-
SPC 190-05	5	190,0	199,6	3	3020	75	-	136	140	42,0	51	42,0	-
SPC 200-05	5	200,0	209,6	3	3535	90	-	136	150	23,5	89	23,5	-
SPC 212-05	5	212,0	221,6	3	3535	90	-	136	160	23,5	89	23,5	-
SPC 224-05	5	224,0	233,6	3	3535	90	-	136	173	23,5	89	23,5	-
SPC 236-05	5	236,0	245,6	3	3535	90	-	136	185	23,5	89	23,5	-
SPC 250-05	5	250,0	259,6	3	3535	90	-	136	198	23,5	89	23,5	-
SPC 265-05	5	265,0	274,6	3	3535	90	-	136	213	23,5	89	23,5	-
SPC 280-05	5	280,0	289,6	3	3535	90	-	136	228	23,5	89	23,5	-
SPC 300-05	5	300,0	309,6	6	3535	90	20	136	247	23,5	89	23,5	170
SPC 315-05	5	315,0	324,6	6	3535	90	20	136	264	23,5	89	23,5	170
SPC 335-05	5	335,0	344,6	6	3535	90	20	136	280	23,5	89	23,5	170
SPC 355-05	5	355,0	364,6	6	3535	90	20	136	304	23,5	89	23,5	170
SPC 375-05	5	375,0	384,6	6	3535	90	20	136	324	23,5	89	23,5	170
SPC 400-05	5	400,0	409,6	5	3535	90	-	136	344	23,5	89	23,5	170
SPC 425-05	5	425,0	434,6	5	4040	100	-	136	369	17	102	17	200
SPC 450-05	5	450,0	459,6	5	4040	100	-	136	394	17	102	17	200
SPC 475-05	5	475,0	484,6	5	4040	100	-	136	419	17	102	17	200
SPC 500-05	5	500,0	509,6	5	4040	100	-	136	444	17	102	17	200
SPC 530-05	5	530,0	539,6	5	4040	100	-	136	474	17	102	17	200
SPC 560-05	5	560,0	569,6	5	4545	110	-	136	504	11	114	11	225
SPC 630-05	5	630,0	639,6	5	5050	125	-	136	574	4,5	127	4,5	245
SPC 710-05	5	710,0	719,6	5	5050	125	-	136	654	4,5	127	4,5	245
SPC 800-05	5	800,0	809,6	5	5050	125	-	136	737	4,5	127	4,5	245
SPC 1000-05	5	1000,0	1009,6	5	5050	125	-	136	937	4,5	127	4,5	245
SPC 1250-05	5	1250,0	1259,6	5	5050	125	-	136	1187	4,5	127	4,5	245