



Polias Dentadas Passo Métrico série AT para Correias "AT"



2



2F

SÉRIE AT 5 (PASSO 5 mm) PARA CORREIAS DE LARGURA 16 mm

Material	Código	Tipo	Dentes	De	Df	Dm	F	L	d	Nº Flange	Kg
ALUMÍNIO UNI 9006 - T6	27 AT 5 12	2F	12	17,85	23,0	10	21	27	-	201	0,02
	27 AT 5 14	2F	14	21,05	25,0	13	21	27	-	203	0,03
	27 AT 5 15	2F	15	22,65	28,0	16	21	27	-	204	0,03
	27 AT 5 16	2F	16	24,20	32,0	18	21	27	-	205	0,04
	27 AT 5 18	2F	18	27,40	32,0	20	21	27	-	205	0,04
	27 AT 5 19	2F	19	29,00	36,0	22	21	27	-	206	0,05
	27 AT 5 20	2F	20	30,60	36,0	23	21	27	-	206	0,06
	27 AT 5 22	2F	22	33,85	38,0	24	21	27	-	207	0,06
	27 AT 5 24	2F	24	37,00	42,0	26	21	27	-	208	0,08
	27 AT 5 25	2F	25	38,55	44,0	26	21	27	-	209	0,08
	27 AT 5 26	2F	26	40,20	44,0	26	21	27	-	209	0,09
	27 AT 5 27	2F	27	41,80	48,0	30	21	27	8	210	0,09
	27 AT 5 28	2F	28	43,35	48,0	32	21	27	8	210	0,09
	27 AT 5 30	2F	30	46,55	51,0	34	21	27	8	211	0,10
	27 AT 5 32	2F	32	49,70	54,0	38	21	27	8	212	0,12
	27 AT 5 36	2F	36	56,05	63,0	38	21	27	8	215	0,16
	27 AT 5 40	2F	40	62,45	66,0	40	21	27	8	216	0,19
	27 AT 5 42	2F	42	65,60	71,0	40	21	27	8	217	0,20
	27 AT 5 44	2	44	68,80	-	45	21	27	8	-	0,23
	27 AT 5 48	2	48	75,15	-	50	21	27	8	-	0,28
	27 AT 5 60	2	60	94,25	-	65	21	27	8	-	0,43

SÉRIE AT 5 (PASSO 5 mm) PARA CORREIAS DE LARGURA 25 mm

Material	Código	Tipo	Dentes	De	Df	Dm	F	L	d	Nº Flange	Kg
ALUMÍNIO UNI 9006 - T6	36 AT 5 12	2F	12	17,85	23,0	10	30	36	-	201	0,03
	36 AT 5 14	2F	14	21,05	25,0	13	30	36	-	203	0,04
	36 AT 5 15	2F	15	22,65	28,0	16	30	36	-	204	0,04
	36 AT 5 16	2F	16	24,20	32,0	18	30	36	-	205	0,05
	36 AT 5 18	2F	18	27,40	32,0	20	30	36	-	205	0,06
	36 AT 5 19	2F	19	29,00	36,0	22	30	36	-	206	0,07
	36 AT 5 20	2F	20	30,60	36,0	23	30	36	-	206	0,08
	36 AT 5 22	2F	22	33,85	38,0	24	30	36	-	207	0,08
	36 AT 5 24	2F	24	37,00	42,0	26	30	36	8	208	0,11
	36 AT 5 25	2F	25	38,55	44,0	26	30	36	8	209	0,12
	36 AT 5 26	2F	26	40,20	44,0	26	30	36	8	209	0,12
	36 AT 5 27	2F	27	41,80	48,0	30	30	36	8	210	0,13
	36 AT 5 28	2F	28	43,35	48,0	32	30	36	8	210	0,14
	36 AT 5 30	2F	30	46,55	51,0	34	30	36	8	211	0,15
	36 AT 5 32	2F	32	49,70	54,0	38	30	36	8	212	0,18
	36 AT 5 36	2F	36	56,05	63,0	38	30	36	8	215	0,23
	36 AT 5 40	2F	40	62,45	66,0	40	30	36	8	216	0,28
	36 AT 5 42	2F	42	65,60	71,0	40	30	36	8	217	0,29
	36 AT 5 44	2	44	68,80	-	45	30	36	8	-	0,31
	36 AT 5 48	2	48	75,15	-	50	30	36	8	-	0,40
	36 AT 5 60	2	60	94,25	-	65	30	36	8	-	0,61