

Carretos simples temperados por indução

3/8" x 7/32"

(06 B1)

Z	de	dp	dm	D ₁	A
13	43,5	39,80	28	10	25
14	46,5	42,80	31	10	25
15	49,5	45,81	34	10	25
16	52,5	48,82	37	10	28
17	55,5	51,83	40	10	28
18	58,6	54,85	43	10	28
19	61,6	57,87	45	10	28
20	64,6	60,89	46	10	28
21	67,6	63,91	48	12	28
22	70,6	66,93	50	12	28
23	73,7	69,95	52	12	28
24	76,7	72,97	54	12	28
25	79,7	76,00	57	12	28
30	94,8	92,12	60	12	28

3/4" x 7/16"

(12 B1)

Z	de	dp	dm	D ₁	A
12	81,8	73,60	52	16	35
13	87,8	79,59	58	16	35
14	93,8	85,61	64	16	35
15	99,8	91,63	70	16	35
16	105,8	97,65	75	16	35
17	111,9	103,67	80	16	35
18	117,9	109,71	80	16	35
19	123,9	115,75	80	16	35
20	130,0	121,78	80	16	35
21	136,0	127,82	90	20	40
22	142,0	133,86	90	20	40
23	148,1	139,90	90	20	40
24	154,1	145,94	90	20	40
25	160,2	152,00	90	20	40
30	190,4	182,25	95	20	40

1/2" x 5/16"

(08 B1)

Z	de	dp	dm	D ₁	A
12	53,9	49,07	33	10	28
13	57,9	53,06	37	10	28
14	61,9	57,07	41	10	28
15	65,9	61,09	45	10	28
16	69,9	65,10	50	12	28
17	74,0	69,11	52	12	28
18	78,0	73,14	56	12	28
19	82,0	77,16	60	12	28
20	86,0	81,19	64	12	28
21	90,1	85,22	68	14	28
22	94,1	89,24	70	14	28
23	98,1	93,27	70	14	28
24	102,1	97,29	70	14	28
25	106,2	101,33	70	14	28
30	126,3	121,50	80	16	30

1" x 17,02mm

(16 B1)

Z	de	dp	dm	D ₁	A
12	109,7	98,14	69	16	40
13	117,7	106,12	78	16	40
14	125,7	114,15	84	16	40
15	133,7	122,17	92	16	40
16	141,8	130,20	100	20	45
17	149,8	138,22	100	20	45
18	157,8	146,28	100	20	45
19	165,9	154,33	100	20	45
20	173,9	162,38	100	20	45
21	182,0	170,43	110	20	50
22	190,1	178,48	110	20	50
23	198,1	186,53	110	20	50
24	206,2	194,59	110	20	50
25	214,2	202,65	110	20	50
30	254,6	243,00	120	20	50

5/8" x 3/8"

(10 B1)

Z	de	dp	dm	D ₁	A
12	68,2	61,34	42	12	30
13	73,2	66,32	47	12	30
14	78,2	71,34	52	12	30
15	83,2	76,36	57	12	30
16	88,3	81,37	60	12	30
17	93,3	86,39	60	12	30
18	98,3	91,42	70	14	30
19	103,3	96,45	70	14	30
20	108,4	101,49	75	14	30
21	113,4	106,52	75	16	30
22	118,4	111,55	80	16	30
23	123,5	116,58	80	16	30
24	128,5	121,62	80	16	30
25	133,6	126,66	80	16	30
30	158,8	151,87	90	20	35

