


Carretos	Z	de	dp	S			D			T		
				dm	D ₁	A	dm	D ₂	A	dm	D ₃	A
1/2" x 5/16" 12,7 x 7,75 mm (08B - 1 - 2 - 3) para corrente de rolo segundo DIN 8187 ISO/R 606 	8	38,0	33,18	20	10	25	20	10	32	20	10	46
	9	42,0	37,13	24	10	25	24	10	32	24	12	46
	10	45,9	41,10	26	10	25	28	10	32	28	12	46
	11	49,9	45,07	29	10	25	32	12	35	32	16	50
	12	53,9	49,07	33	10	28	35	12	35	35	16	50
	13	57,9	53,06	37	10	28	38	12	35	38	16	50
	14	61,9	57,07	41	10	28	42	12	35	42	16	50
	15	65,9	61,09	45	10	28	46	12	35	46	16	50
	16	69,9	65,10	50	12	28	50	16	38	50	16	50
	17	74,0	69,11	52	12	28	54	16	38	54	16	50
	18	78,0	73,14	56	12	28	58	16	38	58	16	50
	19	82,0	77,16	60	12	28	62	16	38	62	16	50
	20	86,0	81,19	64	12	28	66	16	38	66	16	50
	21	90,1	85,22	68	14	28	70	16	40	70	16	55
	22	94,1	89,24	70	14	28	70	16	40	70	16	55
	23	98,1	93,27	70	14	28	70	16	40	70	16	55
	24	102,1	97,29	70	14	28	75	16	40	75	16	55
	25	106,2	101,33	70	14	28	80	16	40	80	16	55
	26	110,2	105,36	70	16	30	85	16	40	85	20	55
	27	114,2	109,40	70	16	30	85	16	40	85	20	55
CARRETO mm Raio dente r ₃ 13 Largura raio C 1,3 Largura dente carreto B ₁ 7,2 Largura dente carreto b ₁ 7 Largura dente carreto B ₂ 21 Largura dente carreto B ₃ 34,9 CORRENTE mm Passo 12,7 Largura interna 7,75 Rolo - Ø 8,51 Material C 43	28	118,3	113,42	70	16	30	90	16	40	90	20	55
	29	122,3	117,46	80	16	30	95	16	40	95	20	55
	30	126,3	121,50	80	16	30	100	16	40	100	20	55
	31	130,4	125,54	90	16	30	100	20	40	110	20	55
	32	134,4	129,56	90	16	30	100	20	40	110	20	55
	33	138,4	133,60	90	16	30	100	20	40	110	20	55
	34	142,5	137,64	90	16	30	100	20	40	110	20	55
	35	146,5	141,68	90	16	30	100	20	40	110	20	55
	36	150,6	145,72	90	16	35	100	20	40	120	25	55
	37	154,6	149,76	90	16	35	100	20	40	120	25	55
	38	158,6	153,80	90	16	35	100	20	40	120	25	55
	39	162,7	157,83	90	16	35	100	20	40	120	25	55
	40	166,7	161,87	90	16	35	100	20	40	120	25	55
	41	172,4	165,91	88	20	42	108	20	55	-	-	-
	42	176,5	169,95	88	20	42	108	20	55	120	25	68
	43	180,5	173,99	88	20	42	108	20	55	-	-	-
	44	184,6	178,03	88	20	42	108	20	55	-	-	-
	45	188,6	182,07	88	20	42	108	20	55	120	25	68
	46	192,6	186,10	88	20	42	108	20	55	120	25	68
	47	196,7	190,14	88	20	42	108	20	55	-	-	-
	48	200,7	194,18	88	20	42	108	20	55	120	25	68
	49	204,8	198,22	88	20	42	108	20	55	-	-	-
	50	208,8	202,26	88	20	42	108	20	55	120	25	68
	51	212,8	206,30	88	20	42	108	20	55	-	-	-
	52	216,9	210,34	88	20	42	108	20	55	-	-	-
	53	220,9	214,37	88	20	42	-	-	-	-	-	-
	54	225,0	218,43	88	20	42	108	20	55	-	-	-
	55	229,0	222,46	88	20	42	108	20	55	-	-	-
	56	233,0	226,50	88	20	42	108	25	55	-	-	-
	57	237,1	230,54	88	20	42	108	25	55	120	25	68
	58	241,1	234,58	88	20	42	108	25	55	120	25	68
	59	245,2	238,62	88	20	42	108	25	55	-	-	-
	60	249,2	242,66	88	20	42	108	25	55	120	25	68
	62	257,3	250,75	88	20	42	108	25	55	-	-	-
	63	261,3	254,80	88	20	42	-	-	-	-	-	-
	64	265,4	258,82	88	20	42	108	25	55	120	25	68
	65	269,4	262,86	88	20	42	108	25	55	-	-	-
	66	273,4	266,90	88	20	42	108	25	55	-	-	-
	68	281,5	274,99	88	20	42	108	25	55	-	-	-
	69	285,6	279,53	88	20	42	-	-	-	-	-	-
	70	289,6	283,07	88	20	42	108	25	55	120	25	68
	72	297,7	291,16	88	20	42	108	25	55	-	-	-
	74	305,8	299,26	88	20	42	-	-	-	-	-	-
	75	309,8	303,27	88	20	42	108	25	55	-	-	-
	76	313,9	307,33	88	20	42	108	25	55	120	25	68
	78	321,9	315,40	108	25	55	-	-	-	-	-	-
	80	330,0	323,48	108	25	55	108	25	55	-	-	-
	85	350,2	343,69	108	25	55	108	25	55	-	-	-
	90	370,4	363,90	108	25	55	-	-	-	-	-	-
	95	390,7	384,11	108	25	55	120	25	55	136	25	68
	100	410,9	404,31	108	25	55	120	25	55	-	-	-
	114	467,4	460,90	108	25	55	120	25	55	-	-	-
	120	491,7	485,16	108	25	55	-	-	-	-	-	-
	125	511,0	505,37	108	25	55	-	-	-	-	-	-

