





Carretos	Z	de	dp	S			D			T		
				dm	D ₁	A	dm	D ₂	A	dm	D ₃	A
3/4" x 7/16" 19,05 x 11,68 mm (12B - 1 - 2 - 3) para corrente de rolo segundo DIN 8187 ISO/R 606	8	58,0	49,78	31	12	30	31	12	45	31	16	65
	9	63,9	55,70	37	12	30	37	12	45	37	16	65
	10	69,8	61,64	42	12	30	42	12	45	42	16	65
	11	75,8	67,61	46	16	35	47	16	50	47	20	70
	12	81,8	73,60	52	16	35	53	16	50	53	20	70
	13	87,8	79,59	58	16	35	59	16	50	59	20	70
	14	93,8	85,61	64	16	35	65	16	50	65	20	70
	15	99,8	91,63	70	16	35	71	16	50	71	20	70
	16	105,8	97,65	75	16	35	77	20	50	77	20	70
	17	111,9	103,67	80	16	35	83	20	50	83	20	70
	18	117,9	109,71	80	16	35	89	20	50	89	20	70
	19	123,9	115,75	80	16	35	95	20	50	95	20	70
	20	130,0	121,78	80	16	35	100	20	50	100	20	70
	21	136,0	127,82	90	20	40	100	20	50	100	20	70
	22	142,0	133,86	90	20	40	100	20	50	100	20	70
	23	148,1	139,90	90	20	40	110	20	50	110	20	70
	24	154,1	145,94	90	20	40	110	20	50	110	20	70
	25	160,2	152,00	90	20	40	120	20	50	120	20	70
	26	166,2	158,04	95	20	40	120	20	50	120	20	70
	27	172,3	164,09	95	20	40	120	20	50	120	20	70
CARRETO mm Raio dente r3 19 Largura raio C 2 Largura dente carreto B ₁ 11,1 Largura dente carreto b ₁ 10,8 Largura dente carreto B ₂ 30,3 Largura dente carreto B ₃ 49,8	28	178,3	170,13	95	20	40	120	20	50	120	20	70
	29	184,4	176,19	95	20	40	120	20	50	120	20	70
	30	190,4	182,25	95	20	40	120	20	50	120	20	70
	31	196,5	188,31	95	20	40	120	20	50	130	25	70
	32	202,5	194,35	95	20	40	120	20	50	130	25	70
	33	208,6	200,40	95	20	40	120	20	50	130	25	70
	34	214,6	206,46	95	20	40	120	20	50	130	25	70
	35	220,7	212,52	95	20	40	120	20	50	130	25	70
	36	226,8	218,58	100	20	40	120	25	50	130	25	70
	37	232,8	224,64	100	20	40	120	25	50	130	25	70
CORRENTE mm Passo 19,05 Largura interna 11,68 Rolo - Ø 12,07 Material C 43	38	238,9	230,69	100	20	40	120	25	50	130	25	70
	39	244,9	236,75	100	20	40	120	25	50	130	25	70
	40	251,0	242,81	100	20	40	120	25	50	130	25	70
	41	258,9	248,87	118	25	61	136	25	62	-	-	-
	42	265,0	254,93	118	25	61	136	25	62	140	25	72
	43	271,1	260,98	118	25	61	136	25	62	-	-	-
	44	277,1	267,03	118	25	61	136	25	62	-	-	-
	45	283,2	273,10	118	25	61	136	25	62	140	25	72
	46	289,2	279,16	118	25	61	136	25	62	-	-	-
	47	295,3	285,21	118	25	61	136	25	62	-	-	-
  	48	301,4	291,27	118	25	61	136	25	62	-	-	-
	49	307,4	297,33	118	25	61	-	-	-	-	-	-
	50	313,5	303,39	118	25	61	136	25	62	140	25	72
	51	319,5	309,45	118	25	61	136	25	62	-	-	-
	52	325,6	315,50	118	25	61	136	25	62	-	-	-
	53	331,6	321,56	118	25	61	-	-	-	-	-	-
	54	337,7	327,64	118	25	61	136	25	62	-	-	-
	55	343,8	333,70	118	25	61	136	25	62	140	25	72
	56	349,8	339,75	118	25	61	136	25	62	-	-	-
	57	355,9	345,81	118	25	61	136	25	62	140	30	75
	58	362,0	351,87	118	25	61	-	-	-	-	-	-
	59	368,0	357,93	118	25	61	-	-	-	-	-	-
	60	374,1	363,99	118	25	61	136	25	62	140	30	75
	61	380,1	369,99	118	25	61	-	-	-	-	-	-
	62	386,2	376,12	118	25	61	-	-	-	-	-	-
	64	398,3	388,24	118	25	61	145	30	63	-	-	-
	65	404,4	394,29	118	25	61	-	-	-	150	30	75
	68	422,6	412,49	-	-	-	145	30	63	-	-	-
	69	428,7	418,55	118	25	61	-	-	-	-	-	-
	70	434,7	424,60	118	25	61	145	30	63	-	-	-
	72	446,8	436,74	118	25	61	145	30	63	150	30	75
	75	465,0	454,91	118	25	61	-	-	-	-	-	-
	76	471,1	460,99	118	30	61	145	30	63	150	30	75
	80	495,3	485,22	-	-	-	145	30	63	-	-	-
	95	586,2	576,17	133	30	62	145	30	63	150	30	75
	100	616,6	606,47	133	30	62	-	-	-	-	-	-
	114	701,4	691,36	133	30	62	-	-	-	-	-	-