


kegelige Bohrung
tapered bore



K/K30

Hauptabmessungen [mm]				Lagertype	Tragzahlen [kN]			Referenzdrehzahlen [min ⁻¹]	Grenzdrehzahlen [min ⁻¹]	
Boundary dimensions [mm]				Designation	Load ratings [kN]			Thermal speed ratings [rpm]	Limited speed ratings [rpm]	
d	D	B	r ₁ , r ₂ min		C _r dyn.	C _{0r} stat.	C _u	n _{Br}	n _G	
85	180	60	3	22317-E-W33	482	603	68	3200	3800	
	180	60	3	22317-E-K-W33	482	603	68	3200	3800	
90	160	40	2	22218-E-W33	308	406	46	3400	5300	
	160	40	2	22218-E-K-W33	308	406	46	3400	5300	
	160	52,4	2	23218-MB-W33	303	412	47	2900	3800	
	160	52,4	2	23218-K-MB-W33	303	412	47	2900	3800	
	190	64	3	22318-E-W33	536	673	74	3700	3800	
	190	64	3	22318-E-K-W33	536	673	74	3000	3800	
	95	170	43	2,1	22219-E-W33	346	464	52	3300	4800
		170	43	2,1	22219-E-K-W33	346	464	52	3300	4800
	200	67	3	22319-E-W33	587	744	81	2800	3400	
	200	67	3	22319-E-K-W33	587	744	81	2800	3400	
100	165	52	2	23120-MB-W33	327	502	56	2900	4000	
	165	52	2	23120-K-MB-W33	327	502	56	2900	4000	
	180	46	2,1	22220-E-W33	379	510	56	3200	4500	
	180	46	2,1	22220-E-K-W33	379	510	56	3200	4500	
	180	60,3	2,1	23220MB-W33	390	532	59	2700	3400	
	180	60,3	2,1	23220-K-MB-W33	390	532	59	2700	3400	
	215	73	3	22320-E-W33	682	842	90	2600	3000	
	215	73	3	22320-E-K-W33	682	842	90	2600	3000	
110	170	45	2	23022-MB-W33	274	447	49,2	3100	4300	
	170	45	2	23022-K-MB-W33	274	447	49,2	3100	4300	